

F9000™ Inversion Table

Specifications:

Features

Knee-high ankle ratchet system is within easy reach for securing the ankle clamps to a comfortable fit, eliminating back strain. The easy to reach ratchet opens and closes with the push of a button, eliminating the need to reach to the ankles to secure the foot clamps

Rotates on a pivot system controlled by weight displacement as a result of arm movements. The table smoothly and easily rotates to any comfortable angle, allowing for oscillation and intermittent traction.

Curved high density foam ankle clamps provide security and comfort

Corner feet increase the A-frame base by 20%, reduce sliding on hard surfaces, and protect floors

Auto locking hinges secure the table to A-frame for improved security and portability

Teflon™ embedded epoxy coated pivot pins provide a life-time of smooth and squeak free rotation

Adjustable roller hinges offer three rates of rotation

Cam-locks improve stability of each setting

Heat treated high quality carbon steel is utilized in key structural components for increased strength

Powder coating is scratch resistant

Chrome features are triple-plated

De-rattler reduces main shaft movement allowing quiet and smooth rotation. The only De-rattler on the market to structurally engage the main shaft

Adjustable and washable nylon table bed

Injection coated rubber hand grips for the ultimate in durability

Folds for storage in seconds

Adjustable tether strap allows maximum angle to be pre-set before inverting

Warranty

5-years

Instructions

Product can be supplied with instructions in a variety of languages, as well as optional English book and instructional video

Assembly

95% pre-assembled, includes tools for assembly

Maximum user height

198 cm (6'6") Easily adjusts for users from 142 to 198 centimeter (4'8" to 6'6"), height markers embossed in both centimeters and inches on main-shaft

Maximum user weight

136 kg (300 lbs)



F9000™ Inversion Table

(Specifications Continued)

Assembled

dimensions	114L x 71W x 147H cm (45 x 28 x 58 inches)
Packaged dimension	Box 1: 127 x 70 x 14 cm (50 x 30 x 5.5 inches)Box 2: 119 x 49.5 x 25 cm (44 x 19.5 x 10 inches)
Packaged weight	Box 1: 26 kg (57 lbs)Box 2: 9.55 kg (21 lbs)
Patents	USA and International apply
Origin	Made in Taiwan

Ratings and Classifications:

UL 2601-1	Classified as UL 2601-1, Medical Electrical Equipment, part I; General Requirements for Safety in accordance with Underwriters Laboratories, Inc. Representative samples of these tables have been evaluated by UL and have successfully met these safety requirements. UL 2601-1 is a very rigorous specification that tests a unit in its extreme use positions. At the maximum height settings, the 136 kg (300 lbs) rated load is tested at the fully inverted position with a 400% safety factor.
CE	CE classified to the Medical Device Directive 93/42/EEC

Optional Accessories:

Over-EZ

Training Handles Designed to assist novice inverters

EZ-Angle

Tether Strap Allows quick interchange between pre-set angles of inversion

